



solis

20th
ANNIVERSARY

Solis Solarator Series

Experience Uninterrupted Power with Solis Energy Storage Inverters

Energy Storage Inverters

S6-EH3P(8-15)K02-NV-YD-L

Three Phase | Low Voltage



Smart Energy Management

- AI intelligently manages charging and discharging based on TOU (Time-of-Use) tariffs
- Seamless integration with VPP and EMS platforms for enhanced energy optimization
- Built-in control for SG-ready heat pumps



High Performance

- Supports three-phase unbalanced output, allowing up to 50% of rated inverter power per phase
- 160% PV input capacity to maximize solar energy utilization
- Switching time < 10ms



Flexible & Scalable

- Compatible with mainstream lithium and lead-acid batteries
- Easily expand system capacity using parallel connections and AC coupling



Simple & Fast Configuration

- 7-inch LCD screen for an intuitive user experience
- Bluetooth app support for quick and easy setup



EnerGo Investment
A jövő energiája



energostore.hu

DATASHEET

S6-EH3P(8-15)K02-NV-YD-L

Models	8K	10K	12K	15K
Input DC (PV side)				
Recommended max. PV array size	16 kW	20 kW	24 kW	30 kW
Max. usable PV input power	12.8 kW	16 kW	19.2 kW	24 kW
Max. input voltage	1000 V			
Rated voltage	550 V			
Start-up voltage	160 V			
MPPT voltage range	200 - 850 V			
Max. input current	20 A / 40 A			40 A / 40 A
Max. short circuit current	30 A / 50 A			50 A / 50 A
MPPT number / Max. input strings number	2 / 3			2 / 4
Battery				
Battery type	Li-ion / Lead-acid			
Battery voltage range	40 - 60 V			
Max. charge / discharge current	180 A	220 A	250 A	290 A
Communication	CAN / RS485			
Output AC (Grid side)				
Rated output power	8 kW	10 kW	12 kW	15 kW
Max. apparent output power	8 kVA	10 kVA	12 kVA	15 kVA
Rated grid voltage	3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V			
Rated grid frequency	50 Hz			
Rated grid output current	12.2 A / 11.5 A	15.2 A / 14.4 A	18.2 A / 17.3 A	22.8 A / 21.7 A
Max. output current	12.2 A	15.2 A	18.2 A	22.8 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)			
THDi	< 3%			
Input AC (Grid side)				
Input voltage range	323 - 460 V			
Max. input current	18.3 A / 17.3 A	22.8 A / 21.7 A	27.3 A / 26.0 A	34.2 A / 32.5 A
Frequency range	45 - 55 Hz / 55 - 65 Hz			
Input Generator				
Max. input power	8 kW	10 kW	12 kW	15 kW
Max. input current	12.2 A	15.2 A	18.2 A	22.8 A
Rated input voltage	3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V			
Rated input frequency	50 Hz			
Output AC (Back-up)				
Rated output power	8 kW	10 kW	12 kW	15 kW
Max. apparent output power	2 times of rated power, 10 s			
Back-up switch time	< 10 ms			
Rated output voltage	3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V			
Rated frequency	50 Hz			
Rated output current	12.2 A / 11.5 A	15.2 A / 14.4 A	18.2 A / 17.3 A	22.8 A / 21.7 A
Max. continuous output current	12.2 A	15.2 A	18.2 A	22.8 A
Max. continuous AC passthrough current	50 A			
THDv (@linear load)	< 3%			
Efficiency				
Max. efficiency	97.5%			
EU efficiency	97.0%			
BAT charged by PV / AC max. efficiency	95.0% / 94.4%			
BAT discharged to AC max. efficiency	94.5%			
Protection				
Anti-islanding protection	Yes			
Output over current protection	Yes			
Short circuit protection	Yes			
DC reverse-polarity protection	Yes			
Surge protection	Yes			
General Data				
Dimensions (W × H × D)	430 × 660 × 305 mm			
Weight	42 kg			
Topology	Non-isolated			
Self-consumption (night)	< 30 W			
Operating ambient temperature range	-40 ~ +60°C			
Ingress protection	IP66			
Noise emission (typical)	< 65 dB(A)			
Cooling concept	Intelligent fan-cooling			
Max. operation altitude	4000 m			
Grid connection standard	NRS 097-2-1, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, SriLanka, EN 50438L, Vietnam, PEA, MEA			
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-3			
Features				
DC connection	MC4 Quick connection plug (PV) & Screw terminal (Battery)			
AC connection	Screw terminal			
Display	7.0" LCD display & Bluetooth + APP			
Communication	CAN, RS485, Ethernet, Optional: Wi-Fi, Cellular, LAN			